

Product Specification Sheet

ERT-F / EF-F

Printable with resin ribbon (FTA-LH...x...) for foil labels

**Permanent, top-coated glossy white polypropylene labels
 on roll for thermal transfer printers**

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	50 +/-3	micron	ISO 534
Adhesive	*	micron	
Liner (glassine)	55 +/-3	micron	ISO 534

Adhesive (acrylic):

		Target	Unit	Test Method
Adhesive strength		14 ±6	N/25 mm	FTM1 -24 hours on glass
Peel Resistance	Stainless Steel	*		
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-30 to +90	°C	

*no information provided by the manufacturer

Certifications: Material meets REACH and RoHS requirements (2015/863/EU). Approved for dry, moist, non fatty foodstuffs according to ISEGA. Compliant with toy security norm EN 71/part 3.

Printability: Suited for thermal transfer printing with resin ribbons (i.e. Armor AXR® 7+, AXR® 8; Labelident Ultra resin, Labelident Premium resin).

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions as well as direct sunlight should be avoided.

Further Information: n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: August 2020.